

Heat pump model	Master Therm	AQ37IC-1, AQ37IC-0
------------------------	---------------------	---------------------------

Heat pump type	Brine/Water
Supplementary heater	No
Heat pump combination heater	Yes

Reference heating season		Average		
Reference water temperature		LOW, 35°C		
Full load heating		Prated [kW]	15,27	
Seasonal efficiency		η_s [%]	196	A+++
Annual electricity consumption		Q_{HE} [kWh]	6185	
Average 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T _j [°C]	P _{dh} [kW]	COP _d (-)	C _{dh} (-)
A	-7	13,65	4,54	0,900
B	2	8,63	5,04	0,900
C	7	5,42	5,60	0,900
D	12	2,62	5,60	0,975
TOL (E)	-10	15,27	4,44	0,900
Tbivalent (F)	-10	15,27	4,44	0,900

Reference heating season		Average		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	13,89	
Seasonal efficiency		η_s [%]	151	A+++
Annual electricity consumption		Q_{HE} [kWh]	7232	
Average 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T _j [°C]	P _{dh} [kW]	COP _d (-)	C _{dh} (-)
A	-7	12,35	3,16	0,900
B	2	8,17	3,92	0,900
C	7	5,00	4,59	0,900
D	12	2,52	4,70	0,978
TOL (E)	-10	13,89	3,00	0,900
Tbivalent (F)	-10	13,89	3,00	0,900

Reference heating season		Warmer		
Reference water temperature		Low, 35°C		
Full load heating		Prated [kW]	15,27	
Seasonal efficiency		η_s [%]	198	
Annual electricity consumption		Q_{HE} [kWh]	3961	
Warmer 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T _j [°C]	P _{dh} [kW]	COP _d (-)	C _{dh} (-)
B	2	15,27	4,44	0,900
C	7	10,33	4,82	0,900
D	12	4,39	5,73	0,900
TOL (E)	2	15,27	4,44	0,900
Tbivalent (F)	2	15,27	4,44	0,900

Heat pump model Master Therm AQ37IC-1, AQ37IC-0

Reference heating season		Warmer		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	13,89	
Seasonal efficiency		η_s [%]	148	
Annual electricity consumption		Q_{HE} [kWh]	4744	
Warmer 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pdh [kW]	COPd (-)	Cdh (-)
B	2	13,89	3,00	0,900
C	7	9,68	3,49	0,900
D	12	4,17	4,59	0,900
TOL (E)	2	13,89	3,00	0,900
Tbivalent (F)	2	13,89	3,00	0,900

Reference heating season		Colder		
Reference water temperature		Low, 35°C		
Full load heating		Prated [kW]	15,27	
Seasonal efficiency		η_s [%]	203	
Annual electricity consumption		Q_{HE} [kWh]	7137	
Colder 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	9,68	4,96	0,900
B	2	5,95	5,60	0,900
C	7	3,87	5,73	0,900
D	12	3,50	5,60	0,981
TOL (E)	-22	15,27	4,44	0,900
Tbivalent (F)	-22	15,27	4,44	0,900
G	-15	12,93	4,73	0,900

Reference heating season		Colder		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	13,99	
Seasonal efficiency		η_s [%]	157	
Annual electricity consumption		Q_{HE} [kWh]	8356	
Colder 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	9,12	3,72	0,900
B	2	5,64	4,49	0,900
C	7	3,39	4,91	0,900
D	12	3,39	4,91	0,983
TOL (E)	-22	13,99	3,07	0,900
Tbivalent (F)	-22	13,99	3,07	0,900
G	-15	12,14	3,36	0,900

Heat pump model		Master Therm	AQ37IC-1, AQ37IC-0
Power consumption in modes other than "active mode"			
Off mode	P_{OFF} [kW]		0,012
Thermostat off mode	P_{TO} [kW]		0,012
Standby mode	P_{SB} [kW]		0,012
Crankcaseheater mode	P_{CK} [kW]		-
Supplementary heater capacity			
Supplementary heater capacity	P_{sup} [kW]		4,5-6
Supplementary heater type	[-]		electricity
Capacity control			
Capacity control			Variable
Sound power level Indoor	L_{WA} [dBA]		48
Sound power level Outdoor	L_{WA} [dBA]		-
Rated brine flow	[m ³ /h]		2,42
Declared load profile / Tapping cycle			
Declared load profile / Tapping cycle			L
Daily electricity consumption	Q_{elec} [kWh]		3,332
Water heating energy efficiency	η_{wh} [%]		86
Temperature controller			
Type	Carel pCO5/pCO5+/uPC, Master Therm custom SW		
Class	II		
Contribution	%		2,0
Temperature controller + Room Terminal			
Type	Carel pCO5/pCO5+/uPC + pAD, Master Therm custom SW		
Class	VI		
Contribution	%		4,0

Heat pump model Master Therm AQ37IC-1, AQ37IC-0

Information sheet			
Temperature application		Low, 35°C	High, 55°C
Space heating energy efficiency class, Average climate	-	A+++	A+++
Nominal heating capacity Pdesign, Average climate	kW	15	14
Space heating seasonal efficiency, Average climate	%	196	151
Space heating annual electricity consumption, Average cl.	kWh	6185	7232
Nominal heating capacity Pdesign, Colder climate	kW	15	14
Space heating seasonal efficiency, Colder climate	%	203	157
Space heating annual electricity consumption, Colder cl.	kWh	7137	8356
Nominal heating capacity Pdesign, Warmer climate	kW	15	14
Space heating seasonal efficiency, Warmer climate	%	198	148
Space heating annual electricity consumption, Warmer cl.	kWh	3961	4744
Sound power level Lwa	dBA	48	

Information sheet for energy efficiency Set with Temperature controller			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC, Class	-	II	II
Controller Carel pCO5/pCO5+/uPC, Contribution	%	2,0	2,0
Set Space heating seasonal efficiency, Average climate	%	198	153
Set Space heating energy efficiency class, Average climate	-	A+++	A+++
Set Space heating seasonal efficiency, Colder climate	%	205	159
Set Space heating seasonal efficiency, Warmer climate	%	200	150

Information sheet for energy efficiency Set with Temperature controller + Room Terminal			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC + pAD, Class	-	VI	VI
Controller Carel pCO5/pCO5+/uPC, +pAD, Contribution	%	4,0	4,0
Set Space heating seasonal efficiency, Average climate	%	200	155
Set Space heating energy efficiency class, Average climate	-	A+++	A+++
Set Space heating seasonal efficiency, Colder climate	%	207	161
Set Space heating seasonal efficiency, Warmer climate	%	202	152