

<b>Heat pump model</b>	<b>Master Therm</b>	<b>BA37I-1, BA37I-0</b>
------------------------	---------------------	-------------------------

Heat pump type	Air/Water
Supplementary heater	Yes
Heat pump combination heater	No

Reference heating season		Average		SCOP 4.49
Reference water temperature		LOW, 35°C		
Full load heating		Prated [kW]	10.93	
Seasonal efficiency		ηs [%]	177	A+++
Annual electricity consumption		QHE [kWh]	5029	
Average 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	TJ [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	9.67	2.64	0.900
B	2	6.10	4.38	0.900
C	7	4.06	6.19	0.900
D	12	4.75	7.62	0.969
TOL (E)	-10	9.04	2.48	0.900
Tbivalent (F)	-7	9.67	2.64	0.900

Reference heating season		Average		SCOP 3.51
Reference water temperature		High, 55°C		
Full load heating	Prated [kW]		10.02	
Seasonal efficiency	ηs [%]		137	A++
Annual electricity consumption	QHE [kWh]		5905	
Average 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	Tj [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	8.86	2.00	0.900
B	2	5.45	3.41	0.900
C	7	3.48	4.94	0.900
D	12	4.08	6.01	0.972
TOL (E)	-10	8.22	1.85	0.900
Tbivalent (F)	-7	8.86	2.00	0.900

Reference heating season			Warmer	
Reference water temperature			Low, 35°C	
Full load heating		Prated [kW]	12.45	
Seasonal efficiency		ηs [%]	249	
Annual electricity consumption		QHE [kWh]	2641	
Warmer 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	Tj [°C]			
B	2	Pdh [kW]	COPd (-)	Cdh (-)
C	7			
D	12			
TOL (E)	-10			
Tbivalent (F)	-7			

<b>Heat pump model</b>	<b>Master Therm</b>	<b>BA37I-1, BA37I-0</b>
------------------------	---------------------	-------------------------

Reference heating season		<b>Warmer</b>		
Reference water temperature		<b>High, 55°C</b>		
Full load heating		<b>Prated [kW]</b>	<b>11.14</b>	
Seasonal efficiency		<b><math>\eta_s</math> [%]</b>	<b>175</b>	
Annual electricity consumption		<b><math>Q_{HE}</math> [kWh]</b>	<b>3340</b>	
<b>Warmer 55°C</b>	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	Tj [°C]	Pdh [kW]	COPd (-)	Cdh (-)
B	2	11.14	2.28	0.900
C	7	7.21	3.79	0.900
D	12	4.51	5.84	0.975
TOL (E)	-10	11.14	2.28	0.900
Tbivalent (F)	-7	11.14	2.28	0.900

Reference heating season		<b>Colder</b>		
Reference water temperature		<b>Low, 35°C</b>		
Full load heating		<b>Prated [kW]</b>	<b>16.31</b>	
Seasonal efficiency		<b><math>\eta_s</math> [%]</b>	<b>135</b>	
Annual electricity consumption		<b><math>Q_{HE}</math> [kWh]</b>	<b>11674</b>	
<b>Colder 35°C</b>	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	Tj [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	9.87	2.78	0.900
B	2	6.18	4.67	0.900
C	7	4.09	6.35	0.900
D	12	4.75	7.62	0.969
TOL (E)	-22	7.55	2.00	0.900
Tbivalent (F)	-7	9.87	2.78	0.900
G	-15	8.44	2.30	0.900

Reference heating season		<b>Colder</b>		
Reference water temperature		<b>High, 55°C</b>		
Full load heating		<b>Prated [kW]</b>	<b>15.21</b>	
Seasonal efficiency		<b><math>\eta_s</math> [%]</b>	<b>113</b>	
Annual electricity consumption		<b><math>Q_{HE}</math> [kWh]</b>	<b>12980</b>	
<b>Colder 55°C</b>	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	Tj [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	9.20	2.27	0.900
B	2	5.89	3.78	0.900
C	7	3.93	5.32	0.900
D	12	4.59	6.36	0.974
TOL (E)	-22	6.95	1.64	0.900
Tbivalent (F)	-7	9.20	2.27	0.900
G	-15	7.82	1.89	0.900

<b>Heat pump model</b>	<b>Master Therm</b>	<b>BA37I-1, BA37I-0</b>
------------------------	---------------------	-------------------------

Power consumption in modes other than "active mode"		
Off mode	P <sub>OFF</sub> [kW]	0.019
Thermostat off mode	P <sub>TO</sub> [kW]	0.019
Standby mode	P <sub>SB</sub> [kW]	0.019
Crankcaseheater mode	P <sub>CK</sub> [kW]	-

Supplementary heater capacity	P <sub>SUP</sub> [kW]	7.5(+7.5)
Supplementary heater type	[-]	electricity

Capacity control		Variable
Sound power level Indoor	L <sub>WA</sub> [dBA]	-
Sound power level Outdoor	L <sub>WA</sub> [dBA]	62
Rated airflow	[m <sup>3</sup> /h]	max.6000

Temperature controller		
Type	Carel pCO5/pCO5+/uPC, Master Therm custom SW	
Class	II	
Contribution	%	2.0

Temperature controller + Room Terminal		
Type	Carel pCO5/pCO5+/uPC + pAD, Master Therm custom SW	
Class	VI	
Contribution	%	4.0

<b>Heat pump model</b>	<b>Master Therm</b>	<b>BA37I-1, BA37I-0</b>
------------------------	---------------------	-------------------------

Information sheet			
Temperature application		Low, 35°C	High, 55°C
Space heating energy efficiency class, Average climate	-	A+++	A++
Nominal heating capacity Pdesign, Average climate	kW	11	10
Space heating seasonal efficiency, Average climate	%	177	137
Space heating annual electricity consumption, Average cl.	kWh	5029	5905
Nominal heating capacity Pdesign, Colder climate	kW	16	15
Space heating seasonal efficiency, Colder climate	%	135	113
Space heating annual electricity consumption, Colder cl.	kWh	11674	12980
Nominal heating capacity Pdesign, Warmer climate	kW	12	11
Space heating seasonal efficiency, Warmer climate	%	249	175
Space heating annual electricity consumption, Warmer cl.	kWh	2641	3340
Sound power level Lwa Outdoor	dBA	62	

Information sheet for energy efficiency Set with Temperature controller			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC, Class	-	II	II
Controller Carel pCO5/pCO5+/uPC, Contribution	%	2.0	2.0
Set Space heating seasonal efficiency, Average climate	%	179	139
Set Space heating energy efficiency class, Average climate	-	A+++	A++
Set Space heating seasonal efficiency, Colder climate	%	137	115
Set Space heating seasonal efficiency, Warmer climate	%	251	177

Information sheet for energy efficiency Set with Temperature controller + Room Terminal			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC + pAD, Class	-	VI	VI
Controller Carel pCO5/pCO5+/uPC, +pAD, Contribution	%	4.0	4.0
Set Space heating seasonal efficiency, Average climate	%	181	141
Set Space heating energy efficiency class, Average climate	-	A+++	A++
Set Space heating seasonal efficiency, Colder climate	%	139	117
Set Space heating seasonal efficiency, Warmer climate	%	253	179